

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	15996.5 cd per klm.
(Luminaire orientation as tested.)	2.5 degrees vertical
	-1.0 degrees horizontal

Beam Spread	At 10% of Imax	23.9V x 20.3H
	At 50% of Imax	12.3V x 10.1H
	At 90% of Imax	4.6V x 4.0H

Beam Flux	Total	1002.0 lumens per klm.
	To 10% of Imax	730.1 lumens per klm.
	To 50% of Imax	359.3 lumens per klm.
	To 90% of Imax	74.5 lumens per klm.

Upward LOR	2.0 %
Downward LOR	98.2 %


Luminaire Efficiency (Light Output Ratio)	100.0 %
---	---------

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 30DEG
Operators: Simon
Test Date: 2019-08-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.417
Humidity: 65.0%
Test Distance: 11.510m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.70V I:0.1038A P:22.121W PF:0.9653 Freq:50.01Hz Lamp Flux:318.354x1 lm		
NAME: ProPoint Sconce L Blue 10Dx5D	TYPE:Sconce	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: Traxon Technologies	SUR.:	Shielding Angle:



DATA OF LAMP		Eff:14.39lm/W	
MODEL	XPE2	Imax(cd)	5093
NOMINAL POWER(W)	24	AVAILABILITY(%)	72.6
RATED VOLTAGE(V)	AC 220	Avai. FLUX(lm)	231.0
NOMINAL FLUX(lm)	318.354	LOR(%)	100.0
LAMPS INSIDE	1	TOTAL FLUX(lm)	318.4
TEST VOLTAGE(V)	AC 220	θ @50% (H,V)	10,12DEG

	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.12	0.17	0.24	0.32	0.41	0.52	0.60	0.66	0.70	0.69	0.64	0.57	0.49	0.39	0.30	0.23	0.18	0.13	7.37	2.44
18	0.14	0.21	0.30	0.42	0.57	0.75	0.90	1.00	1.06	1.04	0.95	0.83	0.68	0.52	0.38	0.28	0.20	0.14	10.4	7.24
16	0.15	0.24	0.38	0.57	0.79	1.07	1.35	1.53	1.63	1.59	1.42	1.21	0.93	0.68	0.48	0.34	0.22	0.14	14.7	12.2
14	0.16	0.26	0.45	0.73	1.07	1.48	1.94	2.25	2.40	2.32	2.05	1.67	1.23	0.86	0.59	0.37	0.22	0.13	20.2	18.3
12	0.15	0.27	0.49	0.84	1.37	1.95	2.58	3.11	3.34	3.21	2.77	2.14	1.51	1.01	0.62	0.36	0.20	0.11	26.0	24.2
10	0.13	0.24	0.47	0.87	1.51	2.37	3.24	4.05	4.40	4.17	3.45	2.52	1.69	1.03	0.58	0.30	0.15	0.08	31.3	29.6
8	0.12	0.22	0.41	0.79	1.48	2.51	3.80	4.90	5.42	5.04	3.94	2.69	1.64	0.89	0.44	0.22	0.12	0.07	34.7	33.1
6	0.11	0.19	0.35	0.68	1.32	2.42	3.95	5.45	6.09	5.56	4.10	2.51	1.35	0.68	0.35	0.19	0.10	0.06	35.4	33.5
4	0.08	0.13	0.24	0.50	1.05	2.10	3.66	5.23	5.93	5.31	3.65	2.04	1.00	0.47	0.23	0.13	0.08	0.05	31.9	30.3
2	0.06	0.09	0.15	0.32	0.71	1.54	2.84	4.18	4.73	4.13	2.76	1.44	0.63	0.28	0.14	0.08	0.06	0.04	24.2	22.6
0	0.05	0.07	0.11	0.19	0.39	0.89	1.67	2.51	2.91	2.53	1.62	0.83	0.35	0.17	0.10	0.07	0.05	0.04	14.6	12.8
-2	0.05	0.06	0.08	0.11	0.19	0.41	0.70	1.12	1.31	1.14	0.75	0.36	0.19	0.11	0.07	0.06	0.04	0.04	6.77	4.62
-4	0.04	0.05	0.06	0.08	0.11	0.17	0.27	0.40	0.45	0.39	0.26	0.17	0.11	0.08	0.06	0.05	0.04	0.03	2.82	0.00
-6	0.04	0.05	0.06	0.07	0.08	0.10	0.12	0.14	0.16	0.15	0.12	0.10	0.08	0.07	0.06	0.05	0.04	0.04	1.52	0.00
-8	0.04	0.05	0.06	0.06	0.07	0.08	0.09	0.09	0.10	0.10	0.09	0.08	0.07	0.06	0.06	0.05	0.05	0.04	1.23	0.00
-10	0.05	0.05	0.06	0.06	0.07	0.07	0.08	0.08	0.08	0.08	0.08	0.08	0.07	0.06	0.06	0.05	0.05	0.05	1.19	0.00
-12	0.06	0.06	0.06	0.07	0.07	0.07	0.08	0.08	0.08	0.08	0.08	0.08	0.07	0.07	0.06	0.06	0.06	0.05	1.23	0.00
-14	0.06	0.06	0.07	0.07	0.07	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.07	0.07	0.07	0.06	0.06	1.32	0.00
-16	0.06	0.06	0.07	0.07	0.07	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.07	0.07	0.07	0.06	0.06	1.32	0.00
-18	0.06	0.06	0.07	0.07	0.07	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.07	0.07	0.07	0.06	0.06	1.32	0.00
	-18	-16	-14	-12	-10	-8	-6	-4	HORIZONTAL (DEG)	4	6	8	10	12	14	16	18			
Φ t	1.59	2.49	4.04	6.75	11.3	18.6	28.0	36.9	40.9	37.6	28.8	19.4	12.2	7.51	4.67	2.95	1.92	1.30	267	---
Φ a	0.00	0.00	0.00	3.96	9.34	17.1	26.7	35.7	39.9	36.6	27.7	17.9	10.3	4.88	1.01	0.00	0.00	0.00	---	231

one-half-peak spread: U:5.3,D:7.0 , L:5.1,R:5.2


NEMA Beam Type: Type 2

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:30DEG
 Operators:Simon
 Test Date:2019-08-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.417
 Humidity:65.0%
 Test Distance:11.510m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.70V I:0.1038A P:22.121W PF:0.9653 Freq:50.01Hz Lamp Flux:318.354x1 lm		
NAME: ProPoint Sconce L Blue 10Dx5D	TYPE:Sconce	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: Traxon Technologies	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:30DEG
Operators:Simon
Test Date:2019-08-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.417
Humidity:65.0%
Test Distance:11.510m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:220.70V I:0.1038A P:22.121W PF:0.9653 Freq:50.01Hz Lamp Flux:318.354x1 lm		
NAME: ProPoint Sconce L Blue 10Dx5D	TYPE:Sconce	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: Traxon Technologies	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 30DEG
Operators: Simon
Test Date: 2019-08-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.417
Humidity: 65.0%
Test Distance: 11.510m [K=1.0000]
Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 30DEG
Operators: Simon
Test Date: 2019-08-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.417
Humidity: 65.0%
Test Distance: 11.510m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.70V I:0.1038A P:22.121W PF:0.9653 Freq:50.01Hz Lamp Flux:318.354x1 lm		
NAME: ProPoint Sconce L Blue 10Dx5D	TYPE:Sconce	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: Traxon Technologies	SUR.:	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:30DEG
 Operators:Simon
 Test Date:2019-08-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.417
 Humidity:65.0%
 Test Distance:11.510m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.70V I:0.1038A P:22.121W PF:0.9653 Freq:50.01Hz Lamp Flux:318.354x1 lm		
NAME: ProPoint Sconce L Blue 10Dx5D	TYPE:Sconce	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: Traxon Technologies	SUR.:	Shielding Angle:

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.61	0.28	0.01	0.00	0.00	0.00	0.00	0.05	0.15	0.40	1.12	2.13	2.72	2.98	3.12	3.23	3.24	2.92	2.40
-170	0.61	0.30	0.06	0.05	0.05	0.06	0.11	0.22	0.45	0.76	1.48	2.85	3.80	3.53	3.18	3.16	3.14	2.95	2.89
-160	0.61	0.33	0.12	0.12	0.10	0.12	0.19	0.33	0.62	1.00	1.47	2.47	3.79	4.29	3.80	3.36	3.23	3.22	3.26
-150	0.61	0.37	0.19	0.18	0.16	0.17	0.24	0.37	0.60	0.91	1.23	1.63	2.41	3.42	4.20	4.45	4.37	4.22	4.16
-140	0.61	0.42	0.27	0.25	0.26	0.23	0.27	0.33	0.43	0.59	0.83	1.12	1.42	1.78	2.26	2.82	3.20	3.45	3.57
-130	0.61	0.46	0.36	0.34	0.38	0.38	0.31	0.30	0.31	0.36	0.46	0.60	0.78	0.99	1.20	1.34	1.43	1.47	1.48
-120	0.61	0.50	0.43	0.44	0.49	0.55	0.48	0.39	0.33	0.31	0.31	0.33	0.38	0.47	0.55	0.59	0.61	0.62	0.62
-110	0.61	0.55	0.52	0.52	0.59	0.65	0.63	0.60	0.56	0.51	0.43	0.36	0.33	0.30	0.30	0.29	0.28	0.28	0.27
-100	0.61	0.59	0.59	0.61	0.65	0.68	0.68	0.69	0.70	0.71	0.67	0.63	0.59	0.55	0.53	0.53	0.53	0.53	0.54
-90	0.61	0.63	0.66	0.69	0.72	0.73	0.74	0.75	0.76	0.77	0.75	0.73	0.71	0.69	0.69	0.71	0.73	0.74	0.76
-80	0.61	0.68	0.73	0.77	0.81	0.85	0.90	0.94	0.98	1.02	1.04	1.04	1.04	1.04	1.06	1.09	1.12	1.15	1.17
-70	0.61	0.71	0.77	0.84	0.91	0.99	1.06	1.11	1.15	1.19	1.20	1.21	1.21	1.21	1.22	1.25	1.27	1.30	1.32
-60	0.61	0.73	0.80	0.88	0.96	1.03	1.07	1.11	1.15	1.21	1.27	1.30	1.32	1.34	1.35	1.39	1.43	1.47	1.49
-50	0.61	0.75	0.82	0.89	0.93	1.00	1.07	1.17	1.28	1.38	1.46	1.51	1.57	1.63	1.68	1.75	1.82	1.87	1.90
-40	0.61	0.76	0.82	0.85	0.89	1.00	1.16	1.32	1.47	1.57	1.69	1.83	2.02	2.27	2.60	3.02	3.51	3.87	3.88
-30	0.61	0.76	0.81	0.80	0.88	1.06	1.27	1.47	1.64	1.81	2.06	2.51	3.61	7.19	15.2	28.7	42.3	48.6	48.4
-20	0.61	0.76	0.79	0.76	0.89	1.12	1.35	1.58	1.80	2.11	2.66	4.28	11.8	32.5	55.8	63.3	68.4	71.9	75.3
-10	0.61	0.76	0.76	0.72	0.89	1.15	1.41	1.67	1.97	2.47	3.48	6.92	15.8	23.8	31.0	41.4	55.7	80.5	90.5
0	0.61	0.75	0.73	0.68	0.86	1.15	1.43	1.71	2.07	2.68	3.80	6.24	10.9	17.8	31.8	79.7	476	2729	4391
10	0.61	0.75	0.72	0.67	0.86	1.13	1.42	1.72	2.10	2.74	3.84	5.86	9.66	18.2	56.8	226	842	1866	2353
20	0.61	0.75	0.72	0.66	0.82	1.08	1.35	1.65	2.00	2.51	3.35	4.66	7.24	16.0	44.4	107	205	291	327
30	0.61	0.74	0.72	0.65	0.74	0.97	1.23	1.49	1.79	2.07	2.48	3.11	4.16	5.81	8.74	16.0	30.1	44.1	51.0
40	0.61	0.74	0.72	0.64	0.66	0.84	1.06	1.26	1.45	1.62	1.80	2.01	2.34	2.77	3.23	3.71	4.20	4.57	4.71
50	0.61	0.73	0.73	0.66	0.62	0.67	0.83	0.97	1.11	1.23	1.34	1.46	1.61	1.76	1.91	2.03	2.12	2.17	2.19
60	0.61	0.71	0.73	0.68	0.61	0.59	0.59	0.66	0.75	0.83	0.91	1.02	1.12	1.21	1.30	1.33	1.36	1.37	1.37
70	0.61	0.69	0.72	0.71	0.67	0.60	0.55	0.53	0.50	0.47	0.48	0.56	0.62	0.68	0.73	0.74	0.74	0.74	0.72
80	0.61	0.66	0.69	0.71	0.71	0.70	0.69	0.66	0.63	0.60	0.54	0.49	0.44	0.41	0.39	0.40	0.40	0.40	0.40
90	0.61	0.63	0.65	0.67	0.69	0.70	0.69	0.68	0.67	0.66	0.65	0.65	0.64	0.63	0.63	0.63	0.64	0.64	0.64
100	0.61	0.59	0.58	0.57	0.56	0.53	0.48	0.43	0.39	0.36	0.34	0.34	0.35	0.36	0.35	0.32	0.30	0.29	0.28
110	0.61	0.54	0.48	0.40	0.33	0.27	0.18	0.12	0.07	0.02	0.02	0.03	0.03	0.04	0.04	0.03	0.03	0.02	0.02
120	0.61	0.49	0.36	0.24	0.14	0.09	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.03	0.05	0.06
130	0.61	0.45	0.26	0.11	0.05	0.02	0.00	0.00	0.00	0.01	0.02	0.03	0.03	0.03	0.03	0.06	0.10	0.12	0.15
140	0.61	0.40	0.17	0.05	0.02	0.00	0.00	0.00	0.01	0.01	0.05	0.08	0.13	0.14	0.19	0.26	0.39	0.51	0.57
150	0.61	0.36	0.10	0.02	0.00	0.00	0.00	0.00	0.00	0.02	0.09	0.20	0.46	0.89	1.36	1.68	1.90	2.07	2.13
160	0.61	0.32	0.06	0.01	0.00	0.00	0.00	0.01	0.02	0.08	0.24	0.79	1.58	2.20	2.57	2.72	2.78	2.83	2.87
170	0.61	0.30	0.03	0.00	0.00	0.00	0.00	0.03	0.09	0.25	0.74	1.66	2.38	2.72	2.90	3.06	3.20	3.17	3.18
180	0.61	0.28	0.01	0.00	0.00	0.00	0.00	0.05	0.15	0.40	1.12	2.13	2.72	2.98	3.12	3.23	3.24	2.92	2.34

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:30DEG
 Operators:Simon
 Test Date:2019-08-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.417
 Humidity:65.0%
 Test Distance:11.510m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.70V I:0.1038A P:22.121W PF:0.9653 Freq:50.01Hz Lamp Flux:318.354x1 lm																	
NAME: ProPoint Sconce L Blue 10Dx5D									TYPE:Sconce						WEIGHT:		
SPEC.:									DIM.:						SERIAL No.:1		
MFR.: Traxon Technologies									SUR.:						Shielding Angle:		

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	2.60	3.16	3.15	3.02	2.99	3.48	3.43	2.02	1.03	0.79	0.49	0.22	0.18	0.24	0.45	0.68	0.77	0.77	
-170	2.91	3.14	3.19	3.18	3.12	3.76	3.47	2.02	1.11	0.85	0.51	0.25	0.20	0.23	0.45	0.68	0.76	0.77	
-160	3.24	3.26	3.31	3.49	4.01	3.93	2.77	1.59	1.07	0.81	0.45	0.25	0.20	0.24	0.47	0.68	0.76	0.77	
-150	4.17	4.29	4.42	4.28	3.63	2.62	1.70	1.21	0.94	0.62	0.36	0.24	0.19	0.27	0.51	0.70	0.75	0.77	
-140	3.48	3.25	2.89	2.32	1.80	1.41	1.13	0.86	0.59	0.39	0.26	0.19	0.20	0.35	0.56	0.71	0.75	0.77	
-130	1.47	1.42	1.36	1.22	1.01	0.79	0.59	0.43	0.30	0.22	0.19	0.19	0.27	0.47	0.63	0.72	0.75	0.77	
-120	0.62	0.61	0.58	0.54	0.43	0.34	0.26	0.21	0.20	0.20	0.23	0.33	0.44	0.58	0.68	0.73	0.74	0.77	
-110	0.27	0.26	0.25	0.25	0.24	0.25	0.26	0.30	0.37	0.43	0.49	0.55	0.60	0.66	0.70	0.72	0.74	0.77	
-100	0.52	0.50	0.49	0.48	0.50	0.54	0.58	0.63	0.67	0.67	0.67	0.67	0.67	0.68	0.70	0.73	0.75	0.77	
-90	0.74	0.72	0.69	0.67	0.67	0.70	0.72	0.75	0.77	0.75	0.74	0.72	0.70	0.70	0.72	0.74	0.75	0.77	
-80	1.14	1.11	1.08	1.04	1.03	1.01	1.00	0.98	0.98	0.92	0.87	0.83	0.81	0.77	0.75	0.75	0.76	0.77	
-70	1.30	1.27	1.24	1.21	1.19	1.18	1.17	1.14	1.11	1.06	1.00	0.94	0.86	0.82	0.81	0.79	0.76	0.77	
-60	1.49	1.49	1.47	1.44	1.39	1.33	1.28	1.23	1.14	1.06	1.00	0.94	0.89	0.87	0.83	0.81	0.78	0.77	
-50	1.86	1.81	1.75	1.69	1.61	1.55	1.48	1.38	1.23	1.08	0.98	0.92	0.89	0.87	0.85	0.82	0.79	0.77	
-40	3.49	2.91	2.40	2.05	1.80	1.63	1.51	1.41	1.29	1.15	0.98	0.91	0.89	0.86	0.85	0.82	0.80	0.77	
-30	41.6	29.1	15.6	7.56	3.56	2.22	1.75	1.49	1.34	1.16	1.10	0.99	0.91	0.86	0.84	0.83	0.81	0.77	
-20	70.9	66.8	58.5	40.3	16.1	4.95	2.43	1.77	1.54	1.41	1.28	1.14	0.97	0.86	0.84	0.82	0.81	0.77	
-10	71.7	48.9	37.0	27.8	17.9	8.23	3.71	2.51	1.97	1.67	1.46	1.26	1.04	0.87	0.83	0.82	0.81	0.77	
0	1357	190	48.5	24.7	14.8	8.22	4.58	3.13	2.36	1.92	1.62	1.35	1.08	0.87	0.82	0.82	0.82	0.77	
10	1576	642	181	46.2	15.0	8.06	4.88	3.29	2.44	1.95	1.62	1.34	1.07	0.85	0.79	0.80	0.81	0.77	
20	287	205	113	51.1	17.3	6.78	4.14	2.98	2.29	1.87	1.55	1.26	1.00	0.80	0.76	0.78	0.80	0.77	
30	45.5	32.0	17.2	8.91	5.57	3.85	2.84	2.28	1.94	1.66	1.38	1.12	0.89	0.74	0.73	0.78	0.80	0.77	
40	4.55	4.16	3.67	3.14	2.65	2.23	1.92	1.72	1.55	1.34	1.14	0.93	0.75	0.68	0.71	0.77	0.79	0.77	
50	2.18	2.14	2.06	1.93	1.76	1.60	1.42	1.29	1.16	1.01	0.85	0.71	0.62	0.64	0.71	0.77	0.78	0.77	
60	1.37	1.36	1.34	1.29	1.20	1.09	0.98	0.85	0.75	0.66	0.58	0.55	0.57	0.65	0.73	0.77	0.77	0.77	
70	0.73	0.73	0.72	0.70	0.64	0.58	0.51	0.47	0.48	0.51	0.53	0.58	0.65	0.71	0.74	0.76	0.76	0.77	
80	0.40	0.41	0.41	0.42	0.43	0.48	0.53	0.59	0.65	0.68	0.69	0.69	0.70	0.71	0.73	0.74	0.75	0.77	
90	0.64	0.65	0.65	0.65	0.66	0.66	0.67	0.67	0.68	0.68	0.69	0.69	0.70	0.71	0.72	0.74	0.75	0.77	
100	0.29	0.30	0.32	0.34	0.34	0.32	0.32	0.31	0.30	0.33	0.37	0.41	0.45	0.53	0.62	0.70	0.74	0.77	
110	0.02	0.03	0.03	0.04	0.04	0.04	0.04	0.02	0.01	0.06	0.09	0.15	0.21	0.37	0.53	0.65	0.73	0.77	
120	0.05	0.04	0.03	0.02	0.02	0.02	0.02	0.02	0.01	0.00	0.00	0.02	0.08	0.27	0.46	0.62	0.72	0.77	
130	0.12	0.09	0.06	0.05	0.05	0.05	0.05	0.04	0.02	0.01	0.00	0.00	0.06	0.22	0.42	0.60	0.72	0.77	
140	0.54	0.44	0.32	0.24	0.19	0.15	0.11	0.06	0.03	0.01	0.00	0.02	0.07	0.19	0.40	0.60	0.72	0.77	
150	2.09	1.96	1.79	1.53	1.12	0.64	0.30	0.12	0.04	0.00	0.03	0.05	0.09	0.18	0.39	0.61	0.73	0.77	
160	2.80	2.72	2.67	2.55	2.27	1.82	1.11	0.42	0.22	0.19	0.13	0.09	0.11	0.18	0.39	0.62	0.74	0.77	
170	3.11	3.08	2.95	2.81	2.68	2.70	2.32	1.30	0.64	0.50	0.31	0.15	0.15	0.20	0.41	0.65	0.75	0.77	
180	2.60	3.16	3.15	3.02	2.99	3.48	3.43	2.02	1.03	0.79	0.49	0.22	0.18	0.24	0.45	0.68	0.77	0.77	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 30DEG
 Operators: Simon
 Test Date: 2019-08-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.417
 Humidity: 65.0%
 Test Distance: 11.510m [K=1.0000]
 Remarks: